

SERIES 19
2" Diameter, 15 Amp




FEATURES

- UL Recognized
- Rugged Construction
- Choice of Termination



DIMENSIONS In inches (and millimeters)



SPECIFICATIONS

Electrical Rating

Rated: UL Recognition: File Number E35289
15 Amps, 120 Vac, non-inductive load.
One Amp, 120 Vdc, non-inductive load.
Additional Grayhill Rating: 7.5 Amps, 220 Vac,
non-inductive load.

This rating is based on the following criteria:
Overload—50 operations at 125% rated ac load
and 150% rated DC load.

Endurance—6000 operations at rated load with
900 Vac dielectric strength before and after test.
Temperature Rise—Not to exceed 30°C when
carrying rated ac load after endurance test.
Contacts will carry 20 Amps at 115 volts AC with
30°C maximum temperature rise.

Contact Resistance: (Measured at 2 Vdc and
approximately 100 mA) for new switch
approximately 10 milliohms.

Insulation Resistance: Approximately 100,000
Mohms. Between mutually insulated parts.

Voltage Breakdown: Approximately 2500 Vac
between mutually insulated parts.

Materials and Finishes

- Rotor Contact:** Silver alloy
- Stator Contact:** Silver alloy
- Shaft:** 303 Stainless steel
- Stop Rivet:** Steel, cadmium-plated
- Mounting Bushing:** Brass, cadmium-plated
- Base and Drive Hub:** Heat resistant, electrical grade phenolic.

- Detent Mechanism:** Brass, silver-plated
- "Faston" Terminal:** Brass, silver-plated
- Solder Terminal:** Brass, silver-plated
- Mounting Hardware:** One mounting nut 9/16" across flats, 3/32" thick and one non-turn washer (see detail) are supplied with each switch.

Additional Characteristics

- Single Pole, Single Deck:** 2 to 11 positions plus common 30° Indexing.
- Contacts:** Non-shorting type
- Stops:** A rivet provides the fixed stop on all switches. Minimum number of positions is 2, and maximum is 11. Terminal 12, the common, is isolated from rotation.
- Rotational Torque:** 30 to 75 ounce-inches on a new switch. Approximately 22 ounce-inches after 25,000 cycles of operation.
- Contact Force:** Approximately 12 ounces

ACCESSORIES

Screw Terminal Adapter

Spring loaded, plug-in adapters for 'Faston' Terminals provide excellent mechanical fit and electrical contact. Adapter material is brass tin-plated. The terminal adapters are available with a 6-32 thread (-1) or 8-32 thread (-2). A 1/4" panhead screw is provided as part of the adapter.



- Part No. SC906-16-32 Thread
- Part No. SC906-28-32 Thread

Non-Turn Washer

Brass, cadmium-plated washer, detailed above may be purchased as a separate item.
Part No. 19C1014.

Control Knobs

See page E-39.

ORDERING INFORMATION

Part Numbers: Designate as follows, using the 2 digits after the dash to indicate the number of positions.

For Faston Terminal:
Use 19101-02UL through 19101-11UL

For Solder Terminal:
Use 19001-02UL through 19001-11UL

Specials: Not available through Distributors. For special shafts, bushings, etc. contact Grayhill.

Available from your local Grayhill Distributor. For prices and discounts, contact a local Sales Office In CHINA (Beijing)
Phone: (010)6851-9097, Fax: (010)6851-5578